

# CYCLO® FAST START STARTING FLUID

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 3.0 10/15/2019 600000001151 Date of first issue: 08/23/2017

### **SECTION 1. IDENTIFICATION**

Product name : DO NOT USE CYC FST STRT FLD 12/10.7 OZ

Product code : C100

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone num: :

ber

: 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : STARTING FLUID

Restrictions on use : Use only outdoors or in a well-ventilated area.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Flammable aerosols : Category 1

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

Category 3 (Central nervous system)

Aspiration hazard : Category 1

**GHS** label elements



## CYCLO® FAST START STARTING FLUID

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 10/15/2019 60000001151 Date of first issue: 08/23/2017 3.0

Hazard pictograms







Signal word Danger

Hazard statements Extremely flammable aerosol.

Harmful if swallowed.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Suspected of damaging the unborn child.

Precautionary statements

#### Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Keep away from heat/sparks/open flames/hot surfaces. No

smokina.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

#### Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

## Disposal:

Dispose of contents/ container to an approved waste disposal plant.



# **CYCLO® FAST START STARTING FLUID**

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 10/15/2019 60000001151 Date of first issue: 08/23/2017 3.0

## Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture Mixture

#### **Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
Heptane, branched, cyclic and linear	426260-76-6	>= 50 - < 70
Ethyl ether	60-29-7	>= 20 - < 30
Carbon dioxide	124-38-9	>= 5 - < 10
n-Heptane	142-82-5	>= 1 - < 5
Ethanol	64-17-5	>= 1 - < 5
Chloroethane	75-00-3	>= 0.1 - < 1
Toluene	108-88-3	>= 0.1 - < 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

#### **SECTION 4. FIRST AID MEASURES**

General advice Move out of dangerous area.

> Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact If on clothes, remove clothes.

Remove contaminated clothing. If irritation develops, get med-

ical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

Immediately flush eye(s) with plenty of water. In case of eye contact

> Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Obtain medical attention.

> Do NOT induce vomiting. Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms

Harmful if swallowed. and effects, both acute and

May be fatal if swallowed and enters airways.



## CYCLO® FAST START STARTING FLUID

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 10/15/2019 60000001151 Date of first issue: 08/23/2017 3.0

delayed Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Suspected of damaging the unborn child.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Dry chemical

Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

Carbon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Remove all sources of ignition. Ensure adequate ventilation.

Avoid breathing dust.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Evacuate personnel to safe areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

**Environmental precautions** Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

#### **SECTION 7. HANDLING AND STORAGE**



# CYCLO® FAST START STARTING FLUID

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 10/15/2019 60000001151 Date of first issue: 08/23/2017 3.0

Advice on protection against

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of

ignition.

Use only explosion-proof equipment.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Take precautionary measures against static discharges.

Avoid contact with skin and eyes.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.

Keep container tightly closed in a dry and well-ventilated

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

No smoking.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Heptane, branched, cyclic and linear	426260-76-6	TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Ethyl ether	60-29-7	TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	400 ppm 1,200 mg/m3	OSHA Z-1
		TWA	400 ppm 1,200 mg/m3	OSHA P0
		STEL	500 ppm 1,500 mg/m3	OSHA P0
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm	NIOSH REL



# **CYCLO® FAST START STARTING FLUID**

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 3.0 10/15/2019 600000001151 Date of first issue: 08/23/2017

Ī	Ī	1	0.000 m a/m2	I
		ST	9,000 mg/m3	NIOSH REL
			30,000 ppm 54,000 mg/m3	
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0
n-Heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		С	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Ethanol	64-17-5	STEL	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
Chloroethane	75-00-3	TWA	100 ppm	ACGIH
		TWA	1,000 ppm 2,600 mg/m3	OSHA Z-1
		TWA	1,000 ppm 2,600 mg/m3	OSHA P0
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0

# **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI



# CYCLO® FAST START STARTING FLUID

Version	Revision Date: 10/15/2019	SDS Number:	Date of last issue: 10/04/2018
3.0		60000001151	Date of first issue: 08/23/2017
i	1	1	

Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

In the case of dust or aerosol formation use respirator with an

approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Flame-resistant clothing

Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not smoke. When using do not eat or drink.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : aerosol

Colour : red

Odour : hydrocarbon-like



## CYCLO® FAST START STARTING FLUID

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 3.0 10/15/2019 600000001151 Date of first issue: 08/23/2017

Odour Threshold : No data available

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : -45 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : 185 °C

Upper explosion limit / Upper

flammability limit

6.7 %(V)

Lower explosion limit / Lower

flammability limit

1.2 %(V)

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.68 g/cm3

Solubility(ies)

Water solubility : slightly soluble

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Molecular weight : No data available

VOC % By Weight : 1 %

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.



## CYCLO® FAST START STARTING FLUID

Version **Revision Date:** SDS Number: Date of last issue: 10/04/2018 10/15/2019 60000001151 Date of first issue: 08/23/2017 3.0

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong oxidizing agents

Hazardous decomposition

products

Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

Inhalation Eve contact Skin contact Ingestion

### **Acute toxicity**

Harmful if swallowed.

**Product:** 

Acute toxicity estimate: 1,726 mg/kg Acute oral toxicity

Method: Calculation method

**Components:** 

Ethyl ether:

LD50 (Rat): 1,200 - 1,700 mg/kg Acute oral toxicity

n-Heptane:

Acute oral toxicity LD50 (Rat): Expected > 5,000 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

LC50 (Rat, male and female): > 29.29 mg/l Acute inhalation toxicity

> Exposure time: 4 h Test atmosphere: vapour

Method: OECD Test Guideline 403

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

LD50 (Rabbit): Expected > 2,000 mg/kg Acute dermal toxicity

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Remarks: Information given is based on data obtained from

similar substances.

**Ethanol:** 

Acute oral toxicity LD50 (Rat): 7,060 mg/kg

Acute inhalation toxicity LC50 (Rat): 117 - 125 mg/l

> Exposure time: 4 h Test atmosphere: vapour

Acute dermal toxicity LDLo (Rabbit): 20 g/kg



# CYCLO® FAST START STARTING FLUID

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 3.0 10/15/2019 600000001151 Date of first issue: 08/23/2017

**Chloroethane:** 

Acute inhalation toxicity : LC50 (Rat): > 19000 ppm

Exposure time: 4 h

Test atmosphere: vapour

Method: OECD Test Guideline 403

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, males): 25.7 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,124 mg/kg

Skin corrosion/irritation

Causes skin irritation.

**Product:** 

Remarks: May cause skin irritation and/or dermatitis.

**Components:** 

Heptane, branched, cyclic and linear:

Result: Irritating to skin.

Ethyl ether:

Result: Irritating to skin.

Carbon dioxide:

Assessment: No skin irritation Result: No skin irritation

n-Heptane:

Result: Irritating to skin.

**Ethanol:** 

Result: Possibly irritating to skin

**Chloroethane:** 

Result: Possibly irritating to skin

Toluene:

Result: Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.



# CYCLO® FAST START STARTING FLUID

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 3.0 10/15/2019 600000001151 Date of first issue: 08/23/2017

**Product:** 

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:** 

Heptane, branched, cyclic and linear:

Result: Possibly irritating to eyes

Ethyl ether:

Result: Irritating to eyes.

Carbon dioxide:

Result: No eye irritation

n-Heptane:

Result: Possibly irritating to eyes

**Ethanol:** 

Result: Irritating to eyes.

**Chloroethane:** 

Result: Possibly irritating to eyes

Toluene:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Heptane, branched, cyclic and linear:

Result: Substance is not considered to be potential skin sensitiser.

n-Heptane:

Test Type: Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Remarks: Information given is based on data obtained from similar substances.

Germ cell mutagenicity

Not classified based on available information.



## CYCLO® FAST START STARTING FLUID

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 3.0 10/15/2019 600000001151 Date of first issue: 08/23/2017

**Components:** 

n-Heptane:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Carcinogenicity

Suspected of causing cancer.

**Components:** 

**Chloroethane:** 

Carcinogenicity - Assess-

ment

Limited evidence of carcinogenicity in animal studies

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Suspected of damaging the unborn child.

**Components:** 

Toluene:

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

**Components:** 

Heptane, branched, cyclic and linear:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

Ethyl ether:

Assessment: May cause drowsiness or dizziness.

n-Heptane:

Assessment: May cause drowsiness or dizziness.

**Ethanol:** 

Assessment: May cause drowsiness or dizziness.



## CYCLO® FAST START STARTING FLUID

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 3.0 10/15/2019 600000001151 Date of first issue: 08/23/2017

Toluene:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

**Components:** 

Toluene:

Exposure routes: Inhalation

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects

on color vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity** 

May be fatal if swallowed and enters airways.

**Components:** 

Heptane, branched, cyclic and linear:

May be fatal if swallowed and enters airways.

n-Heptane:

May be fatal if swallowed and enters airways.

Toluene:

May be fatal if swallowed and enters airways.

**Further information** 

**Product:** 

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vom-

iting.

**SECTION 12. ECOLOGICAL INFORMATION** 

**Toxicity** 

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.



# CYCLO® FAST START STARTING FLUID

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 3.0 10/15/2019 600000001151 Date of first issue: 08/23/2017

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### International Regulations

IATA-DGR

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 Packing instruction (cargo : 203

aircraft)

Packing instruction : 203

(passenger aircraft)

**IMDG-Code** 

UN number : UN 1950 Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : no

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **National Regulations**

49 CFR

UN/ID/NA number : UN 1950 Proper shipping name : Aerosols

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 ERG Code : 126 Marine pollutant : no

## **SECTION 15. REGULATORY INFORMATION**

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Ethyl ether	60-29-7	100	345



## CYCLO® FAST START STARTING FLUID

Version Revision Date: SDS Number: Date of last issue: 10/04/2018 3.0 10/15/2019 600000001151 Date of first issue: 08/23/2017

Toluene	108-88-3	100	100 (F005)
Benzene	71-43-2	10	10 (D018)
Ethyl ether	60-29-7	100	100 (F003)
Methanol	67-56-1	100	100 (F003)

## SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Sulfur dioxide	7446-09-5	500	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

## SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

Carcinogenicity
Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## California Prop. 65

WARNING: This product can expose you to chemicals including Chloroethane, Naphthalene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Methanol, Sulfur dioxide, Benzene, Methyl chloride, n-Hexane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



# **CYCLO® FAST START STARTING FLUID**

Version 3.0

Revision Date: 10/15/2019


SDS Number: 60000001151

Date of last issue: 10/04/2018 Date of first issue: 08/23/2017

### **SECTION 16. OTHER INFORMATION**

### **Further information**

#### NFPA:



Special hazard.

Revision Date : 10/15/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN