

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
Date of first issue: 08/28/2017

SECTION 1. IDENTIFICATION

Product name : CYCLO RUBBERIZED AERO UNDERCOAT 12/16FOZ
Product code : C35

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC
Address : Dallas TX 75225
Email Address : EHS@niteoproducts.com
Telephone : 1-844-696-4836
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : UNDERCOATS
Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable aerosols : Category 1
Skin irritation : Category 2
Eye irritation : Category 2A
Carcinogenicity : Category 2
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision))
Aspiration hazard : Category 1

GHS label elements

CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
Date of first issue: 08/28/2017

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: Extremely flammable aerosol.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
Suspected of damaging the unborn child.
May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

Precautionary statements

: **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF ON SKIN: Wash with plenty of soap and water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.

Storage:
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:
Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
Date of first issue: 08/28/2017

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration (% w/w) |
|----------------|-----------|-----------------------|
| Limestone | 1317-65-3 | >= 30 - < 50 |
| Toluene | 108-88-3 | >= 10 - < 20 |
| Methyl acetate | 79-20-9 | >= 10 - < 20 |
| Acetone | 67-64-1 | >= 5 - < 10 |
| Carbon Black | 1333-86-4 | >= 0.1 - < 1 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and : May be fatal if swallowed and enters airways.
Causes skin irritation.

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
Date of first issue: 08/28/2017

delayed Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure if inhaled.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
Dry chemical
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
Date of first issue: 08/28/2017

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Take precautionary measures against static discharges.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|-----------|--------------------------------|--|-----------|
| Limestone | 1317-65-3 | TWA (total dust) | 15 mg/m ³ | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m ³ | OSHA Z-1 |
| | | TWA (Total dust) | 15 mg/m ³ | OSHA P0 |
| | | TWA (respirable dust fraction) | 5 mg/m ³ | OSHA P0 |
| | | TWA (Respirable) | 5 mg/m ³ (Calcium car- | NIOSH REL |

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
 Date of first issue: 08/28/2017

| | | | | |
|----------------|-----------|--------------------------|---------------------------------|-----------|
| | | | bonate) | |
| | | TWA (total) | 10 mg/m3 (Calcium carbonate) | NIOSH REL |
| Toluene | 108-88-3 | TWA | 20 ppm | ACGIH |
| | | TWA | 100 ppm 375 mg/m3 | NIOSH REL |
| | | ST | 150 ppm 560 mg/m3 | NIOSH REL |
| | | TWA | 200 ppm | OSHA Z-2 |
| | | CEIL | 300 ppm | OSHA Z-2 |
| | | Peak | 500 ppm (10 minutes) | OSHA Z-2 |
| | | TWA | 100 ppm 375 mg/m3 | OSHA P0 |
| | | STEL | 150 ppm 560 mg/m3 | OSHA P0 |
| Methyl acetate | 79-20-9 | TWA | 200 ppm | ACGIH |
| | | STEL | 250 ppm | ACGIH |
| | | TWA | 200 ppm 610 mg/m3 | NIOSH REL |
| | | ST | 250 ppm 760 mg/m3 | NIOSH REL |
| | | TWA | 200 ppm 610 mg/m3 | OSHA Z-1 |
| | | TWA | 200 ppm 610 mg/m3 | OSHA P0 |
| | | STEL | 250 ppm 760 mg/m3 | OSHA P0 |
| Acetone | 67-64-1 | TWA | 250 ppm | ACGIH |
| | | STEL | 500 ppm | ACGIH |
| | | TWA | 250 ppm 590 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 2,400 mg/m3 | OSHA Z-1 |
| | | TWA | 750 ppm 1,800 mg/m3 | OSHA P0 |
| | | STEL | 1,000 ppm 2,400 mg/m3 | OSHA P0 |
| Carbon Black | 1333-86-4 | TWA (Inhalable fraction) | 3 mg/m3 | ACGIH |
| | | TWA | 3.5 mg/m3 | NIOSH REL |
| | | TWA | 3.5 mg/m3 | OSHA Z-1 |
| | | TWA | 3.5 mg/m3 | OSHA P0 |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sam-pling time | Permissible concentra-tion | Basis |
|------------|----------|--------------------|---------------------|----------------------------------|----------------------------|-----------|
| Toluene | 108-88-3 | Toluene | In blood | Prior to last shift of work-week | 0.02 mg/l | ACGIH BEI |

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
Date of first issue: 08/28/2017

| | | | | | | |
|---------|---------|----------|-------|--|---------------------|-----------|
| | | Toluene | Urine | End of shift (As soon as possible after exposure ceases) | 0.03 mg/l | ACGIH BEI |
| | | o-Cresol | Urine | End of shift (As soon as possible after exposure ceases) | 0.3 mg/g Creatinine | ACGIH BEI |
| Acetone | 67-64-1 | Acetone | Urine | End of shift (As soon as possible after exposure ceases) | 25 mg/l | ACGIH BEI |

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
In the case of dust or aerosol formation use respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Flame-resistant clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.1 | 01/07/2021 | 600000001239 | Date of first issue: 08/28/2017 |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|--|---|----------------------------------|
| Appearance | : | aerosol |
| Colour | : | black |
| Odour | : | solvent-like |
| Odour Threshold | : | No data available |
| pH | : | No data available |
| Melting point/range | : | No data available |
| Boiling point/boiling range | : | No data available |
| Flash point | : | -104.45 °C Method: closed cup |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Self-ignition | : | No data available |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapour pressure | : | No data available |
| Relative vapour density | : | No data available |
| Density | : | 1.122 g/cm ³ |
| Solubility(ies) | | |
| Water solubility | : | negligible |
| Partition coefficient: n-octanol/water | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity | | |
| Viscosity, kinematic | : | No data available |
| Molecular weight | : | No data available |
| VOC % By Weight | : | 37.48 % |

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
Date of first issue: 08/28/2017

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Eye contact
Skin contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 129.91 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Limestone:

Acute oral toxicity : LD50 (Rat): 6,450 mg/kg

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, males): 25.7 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,124 mg/kg

Methyl acetate:

Acute oral toxicity : LD50 (Rat, male): 6,482 mg/kg

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
Date of first issue: 08/28/2017

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rabbit): > 49.2 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Acetone:

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 7,426 mg/kg

Carbon Black:

Acute oral toxicity : LD50 (Rat): 8,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Limestone:

Result: Possibly irritating to skin

Toluene:

Result: Irritating to skin.

Methyl acetate:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Possibly irritating to skin

Acetone:

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

Carbon Black:

Species: Rabbit

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.1 | 01/07/2021 | 600000001239 | Date of first issue: 08/28/2017 |

Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Limestone:

Result: Possibly irritating to eyes

Toluene:

Result: Irritating to eyes.

Methyl acetate:

Species: Rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

Acetone:

Result: Irritating to eyes.

Assessment: Irritating to eyes.

Carbon Black:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Toluene:

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Not a skin sensitizer.

Methyl acetate:

Assessment: Does not cause skin sensitisation.

Carbon Black:

Test Type: Buehler Test

**CYCLO® RUBBERIZED AEROSOL
UNDERCOAT**

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
Date of first issue: 08/28/2017

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Toluene:

Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

Methyl acetate:

Target Organs: Central nervous system
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Acetone:

Exposure routes: Inhalation
Target Organs: Nervous system
Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

Components:

Toluene:

Exposure routes: Inhalation
Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)
Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Methyl acetate:

Species: Rat
NOAEL: 1.05 mg/l
Application Route: Inhalation
Test atmosphere: dust/mist
Exposure time: N11.00322320
Method: OECD Test Guideline 412

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Toluene:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
Date of first issue: 08/28/2017

Acetone:

May be harmful if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1

SAFETY DATA SHEET



CYCLO® RUBBERIZED AEROSOL UNDERCOAT

Version 1.1 Revision Date: 01/07/2021 SDS Number: 600000001239 Date of last issue: -
Date of first issue: 08/28/2017


California Prop. 65

WARNING: This product can expose you to chemicals including Carbon Black, Silica, crystalline (Quartz), Ethylbenzene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Methanol, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 01/07/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN