

# Technical Bulletin

## Important Assembly Procedure

---

### 2007-2011 Jeep Wrangler 3.8

**Product:** LuK clutch kit #01-046 (only Jeep Wrangler 3.8L)

**Issue:** Clutch cover / pressure plate will not reach the flywheel dowel pins for alignment.

**Solution:** This LuK clutch assembly is designed to use the mounting bolts provided in packaging.

**Procedure:** Remove dowel pins from flywheel (recommended, but not necessary)

Place clutch assembly into mounting position on the flywheel.

Using the shoulder bolts provided, center each bolt in the pressure plate mounting holes and thread by hand until snug.

Finish tightening and torque to OE vehicle specifications.

If you have questions about this product, call our technical hotline 8:00 a.m. to 6:00 p.m. ET Monday through Friday:

In the United States and Canada: 1-800-274-5001. In Mexico: 01-800-8000-585.

Copies of in-package literature, diagnostic and installation instructions, and product information are available online at [www.repxpert.us](http://www.repxpert.us), [www.repxpert.ca](http://www.repxpert.ca), or [www.repxpert.mx](http://www.repxpert.mx). Registration is free!

## Importante procedimiento de montaje

---

### 2007-2011 Jeep Wrangler 3.8

**Producto:** LuK Kit de Embrague #01-046 (solo Jeep Wrangler 3.8L)

**Problema:** La cubierta del embrague / el plato de presión no alcanzará los pasadores guía del volante para la alineación.

**Solución:** El LuK Kit de Embrague está diseñado para utilizar los pernos de montaje incluidos en el empaque.

**Procedimiento:** Quite los pasadores guía del volante (recomendado, pero no necesario)

Coloque el embrague en la posición de montaje sobre el volante.

Usando los pernos de reborde proporcionados, centre cada uno en los orificios de montaje del plato de presión y enrosque con la mano hasta que queden ajustados.