

SAFETY DATA SHEET



MOTOR MEDIC® BRAKE FLUID DOT 3

Version 1.0 Revision Date: 01/02/2019 SDS Number: 600000001626 Date of last issue: -
Date of first issue: 01/02/2019

SECTION 1. IDENTIFICATION

Product name : MM BF SUPER HD DOT3 12/32OZ
Product code : M4332

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC
Address : Dallas TX 75225
Email Address : EHS@niteoproducts.com
Telephone : 1-844-696-4836
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : BRAKE FLUID
Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Serious eye damage : Category 1
Specific target organ toxicity - repeated exposure (Oral) : Category 2 (Kidney)

GHS label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : Causes serious eye damage.
May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

Precautionary statements : **Prevention:**
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wear eye protection/ face protection.

MOTOR MEDIC® BRAKE FLUID DOT 3

Version 1.0 Revision Date: 01/02/2019 SDS Number: 600000001626 Date of last issue: -
Date of first issue: 01/02/2019

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Get medical advice/ attention if you feel unwell.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration (% w/w) |
|------------------------------------|-----------|-----------------------|
| Triethylene glycol monobutyl ether | 143-22-6 | >= 15 - <= 50 |
| Diethylene glycol | 111-46-6 | >= 15 - <= 25 |
| Diethylene glycol monobutyl ether | 112-34-5 | >= 5 - <= 15 |
| Ethanol, 2-(2-propoxyethoxy)- | 6881-94-3 | >= 2 - <= 5 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
- If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms : Causes serious eye damage.

SAFETY DATA SHEET



MOTOR MEDIC® BRAKE FLUID DOT 3

Version 1.0 Revision Date: 01/02/2019 SDS Number: 600000001626 Date of last issue: -
Date of first issue: 01/02/2019

and effects, both acute and delayed May cause damage to organs through prolonged or repeated exposure if swallowed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
 - Unsuitable extinguishing media : High volume water jet
 - Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
 - Hazardous combustion products : Carbon oxides
 - Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
 - Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
 - Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid breathing dust.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
 - Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
 - Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
 - Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national
-

MOTOR MEDIC® BRAKE FLUID DOT 3

Version 1.0 Revision Date: 01/02/2019 SDS Number: 600000001626 Date of last issue: -
Date of first issue: 01/02/2019

regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-----------------------------------|----------|------------------------------------|--|---------|
| Diethylene glycol | 111-46-6 | TWA | 10 mg/m ³ | US WEEL |
| Diethylene glycol monobutyl ether | 112-34-5 | TWA (Inhalable fraction and vapor) | 10 ppm | ACGIH |

Hazardous components without workplace control parameters

| Components | CAS-No. |
|------------------------------------|-----------|
| Triethylene glycol monobutyl ether | 143-22-6 |
| Ethanol, 2-(2-propoxyethoxy)- | 6881-94-3 |

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles and face shield when there is potential for exposure of the eyes or face to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.

SAFETY DATA SHEET



MOTOR MEDIC® BRAKE FLUID DOT 3

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 01/02/2019 | 600000001626 | Date of first issue: 01/02/2019 |

When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|--|---|-------------------|
| Appearance | : | liquid |
| Colour | : | amber |
| Odour | : | ether-like |
| Odour Threshold | : | not determined |
| pH | : | 10.5 |
| Melting point/freezing point | : | not determined |
| Boiling point/boiling range | : | 205 °C |
| Flash point | : | 203 °C |
| Evaporation rate | : | not determined |
| Flammability (solid, gas) | : | No data available |
| Self-ignition | : | not determined |
| Upper explosion limit / Upper flammability limit | : | not determined |
| Lower explosion limit / Lower flammability limit | : | not determined |
| Vapour pressure | : | not determined |
| Relative vapour density | : | not determined |
| Density | : | not determined |
| Solubility(ies) | | |
| Water solubility | : | not determined |
| Partition coefficient: n-octanol/water | : | not determined |
| Decomposition temperature | : | not determined |
| Viscosity | | |
| Viscosity, dynamic | : | not determined |
| Viscosity, kinematic | : | not determined |
| Molecular weight | : | Not applicable |

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET



MOTOR MEDIC® BRAKE FLUID DOT 3

Version 1.0 Revision Date: 01/02/2019 SDS Number: 600000001626 Date of last issue: -
Date of first issue: 01/02/2019

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Hazardous polymerisation does not occur.

Conditions to avoid : No data available

Incompatible materials : Strong oxidizing agents
Strong acids
Strong bases

Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Eye contact
Skin contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: 3,723 mg/kg
Method: Calculation method

Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be considered toxic by ingestion.

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Remarks: Skin absorption of this material (or a component) may be increased through injured skin.

Components:

Triethylene glycol monobutyl ether:

Acute oral toxicity : LD50 (Rat): 5,300 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 3,502 mg/kg

Diethylene glycol:

Acute oral toxicity : LD50 (Humans): Expected 1,120 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET



MOTOR MEDIC® BRAKE FLUID DOT 3

Version 1.0 Revision Date: 01/02/2019 SDS Number: 600000001626 Date of last issue: -
Date of first issue: 01/02/2019

Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

Diethylene glycol monobutyl ether:

Acute oral toxicity : LD50 (Rat): 3,305 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2,734 mg/kg

Ethanol, 2-(2-propoxyethoxy)-:

Acute oral toxicity : LD50 (Rat): 6,661 mg/kg

Acute dermal toxicity : LD50 (Guinea pig): 5,048 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Triethylene glycol monobutyl ether:

Result: No skin irritation

Diethylene glycol:

Species: human skin

Result: Possibly irritating to skin

Diethylene glycol monobutyl ether:

Result: Possibly irritating to skin

Ethanol, 2-(2-propoxyethoxy)-:

Species: Rabbit

Result: Possibly irritating to skin

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Components:

Triethylene glycol monobutyl ether:

Result: Irreversible effects on the eye

Diethylene glycol:

Species: Rabbit

Result: Possibly irritating to eyes

MOTOR MEDIC® BRAKE FLUID DOT 3

Version 1.0 Revision Date: 01/02/2019 SDS Number: 600000001626 Date of last issue: -
Date of first issue: 01/02/2019

Diethylene glycol monobutyl ether:

Result: Irritating to eyes.

Ethanol, 2-(2-propoxyethoxy)-:

Species: Rabbit

Result: Irritating to eyes.

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Diethylene glycol:**

Test Type: Maximisation Test

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Did not cause sensitisation on laboratory animals.

Diethylene glycol monobutyl ether:

Test Type: Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Ethanol, 2-(2-propoxyethoxy)-:

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:**Diethylene glycol:**

Genotoxicity in vitro : Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 479
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Method: OECD Test Guideline 474
Result: negative

Diethylene glycol monobutyl ether:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Result: In vivo tests did not show mutagenic effects

MOTOR MEDIC® BRAKE FLUID DOT 3

Version 1.0 Revision Date: 01/02/2019 SDS Number: 600000001626 Date of last issue: -
Date of first issue: 01/02/2019

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Diethylene glycol monobutyl ether:

Effects on foetal development : Remarks: No teratogenic effects

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

Components:

Diethylene glycol:

Exposure routes: Ingestion

Target Organs: Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Diethylene glycol monobutyl ether:

NOAEL: 250 mg/kg

LOAEL: 1,000 mg/kg

Application Route: Oral

Target Organs: Blood

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

SAFETY DATA SHEET



MOTOR MEDIC® BRAKE FLUID DOT 3

Version 1.0 Revision Date: 01/02/2019 SDS Number: 600000001626 Date of last issue: -
Date of first issue: 01/02/2019

SECTION 12. ECOLOGICAL INFORMATION

Toxicity
Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods
Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR
Not regulated as a dangerous good

IMDG-Code
Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as supplied.

National Regulations

49 CFR
Not regulated as a dangerous good

49 CFR
Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|----------------|----------|--------------------|-----------------------------|
| Diethanolamine | 111-42-2 | 100 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SAFETY DATA SHEET



MOTOR MEDIC® BRAKE FLUID DOT 3

Version 1.0 Revision Date: 01/02/2019 SDS Number: 600000001626 Date of last issue: -
Date of first issue: 01/02/2019

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

| | | |
|-------------------------------------|----------|-----------------|
| Triethylene glycol mono-butyl ether | 143-22-6 | >= 15 - <= 50 % |
| Triethylene glycol monoethyl ether | 112-50-5 | >= 10 - <= 15 % |
| Diethylene glycol mono-butyl ether | 112-34-5 | >= 5 - <= 15 % |


California Prop. 65

WARNING: This product can expose you to chemicals including Diethanolamine, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 01/02/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET



MOTOR MEDIC® BRAKE FLUID DOT 3

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 01/02/2019 | 600000001626 | Date of first issue: 01/02/2019 |

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN