

SAFETY DATA SHEET

This safety data sheet complies with the requirements of: OSHA Hazard Communication Standard (29 CFR 1910.1200)

Product Name: Idemitsu ATF Type-HP, 12 x 1 Quart Case **Revision Date:** 09-Feb-2021

Product Code: 30040099-75000C020 Revision Number: 4

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE

COMPANY/UNDERTAKING

1.1 Product identifier

Product Name: Idemitsu ATF Type-HP, 12 x 1 Quart Case

Other means of identification

Product Code: 30040099-75000C020

1.2 Recommended use of the chemical and restrictions on use

Recommended Use: Automotive Lubricant

1.3 Details of the supplier of the safety data sheet

Manufactured by: Idemitsu Lubricants America Corporation

701 Port Rd., Jeffersonville, IN. 47130

Telephone: 1-(812) 284-3300 Business hours: 8am-4:30pm est

Email: Ila.sds@idemitsu.com

24 Hour Emergency Phone Number: Within USA and Canada: 1 800-424-9300

Outside USA and Canada: + 1 703-741-5970

(collect calls accepted)

2. HAZARDS IDENTIFICATION

2.1 Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin sensitization Category 1

2.2 Label elements



Signal word Warning

Hazard Statements H317 - May cause an allergic skin reaction

Precautionary Statements - Prevention P261 - Avoid breathing dust, fume, gas, mist, vapors, or spray

P280 - Wear protective gloves

P272 - Contaminated work clothing should not be allowed out of

Revision Date: 09-Feb-2021

the workplace

Precautionary Statements - Response P362 + P364 - Take off all contaminated clothing and wash it

before reuse

Skin P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P363 - Wash contaminated clothing before reuse

P333 + P313 - If skin irritation or rash occurs: Get medical

advice/attention

Precautionary Statements - Disposal P501 - Dispose of contents/ container to an approved waste

disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

2.3 Other information

Other hazards Toxic to aquatic life

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixture

Hazardous Components

Chemical name	CAS-No	weight-%	US GHS Classification	Notes
Long chain alkyl amine alkylene	64051-50-9	<1	Skin Sens. 1B (H317)	
amine				
Alkyl ester carboxylic acid	68015-93-0	<1	Skin Irrit. 2 (H315)	
			Eye Dam. 1 (H318)	
			Skin Sens. 1 (H317)	
			Aquatic Chronic 3	
			(H412)	

Non-Hazardous Components

Chemical name	CAS-No	weight-%
Lubricating Base Stocks	Mixture	80-90

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

4.1 First Aid Measures

General Advice If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for

medical treatment.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before re-use. Call a physician

immediately.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation

Revision Date: 09-Feb-2021

persists: Get medical advice or attention.

Inhalation Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give

oxygen. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty

lean forward to reduce the risk of aspiration. If symptoms persist, call a physician.

Protection of First-aidersUse personal protective equipment. Avoid contact with eyes, skin and clothing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms See Section 11 for additional Toxicological information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties NFPA: Class IIIB Combustible Liquid

5.1 Suitable extinguishing media Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment

Unsuitable Extinguishing Media:Do not use a solid water stream as it may scatter and spread fire.

5.2 Specific Hazards Arising from the Chemical Keep product and empty container away from heat and sources

of ignition.

Hazardous combustion products During a fire, smoke may contain the original material in addition

to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and

Revision Date: 09-Feb-2021

are not limited to: Carbon oxides

Calcium Oxides (CaOx) Nitrogen oxides (NOx) Oxides of Phosphorus Sulphur oxides

5.3 Protective Equipment and Precautions for Firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal

protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of

ignition.

6.2. Environmental precautions

Environmental Precautions See section 12 for additional ecological information. Prevent further leakage or spillage if

safe to do so. Prevent product from entering drains. Do not allow into any sewer, on the ground or into any body of water. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into

waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Methods for Clean-up Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth,

diatomaceus earth, vermiculite) and place in container for disposal according to local /

national regulations (see section 13).

Spill Management

LARGE SPILLS Eliminate sources of ignition. Prevent additional discharge of material if possible to do so

without hazard. For small spills implement cleanup procedures; for large spills implement

cleanup procedures and, if in public area, keep public away and advise authorities.

WATER SPILLS Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand

or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure

conformity to local disposal regulations.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling Avoid contact with eyes, skin and clothing. Remove and wash

contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe vapors, spray, or mist. Use personal protection recommended in

the SDS.

Safe Handling Advice Handle in accordance with good industrial hygiene and safety

practices. Take precautionary measures against static

discharges.

7.2. Conditions for safe storage, including any incompatibilities

Keep in properly labeled containers. Keep container tightly closed Storage

in a dry and well-ventilated place.

Revision Date: 09-Feb-2021

Technical measures/Precautions Ensure adequate ventilation.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Guidelines

Chemical name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m ³	TWA: 5 mg/m ³		TWA 5 mg/m ³ ST 10 mg/m ³			

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal Protective Equipment

Eye/face protection Safety glasses equipped with side shields are recommended as minimum protection in

industrial settings. If splashes are likely to occur wear tight fitting safety goggles and/or

face-shield.

Wear protective gloves/clothing. Long sleeved clothing. Choose the appropriate protective Skin protection

clothing and gloves based on the tasks being performed to avoid exposed skin surfaces.

Glove Type: Neoprene, Nitriles

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

> respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly. **General Hygiene Considerations**

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Red / Clear **Appearance** Physical state Liquid Mild Odor

Odor Threshold No information available

Not applicable Melting point / melting range Not applicable

No information available Boiling point / boiling range

> 174 °C / 345.2 °F COC ASTM D92 **Flash Point**

30040099-75000C020 - Idemitsu ATF Type-HP, 12 x 1 Quart Case

No information available

Revision Date: 09-Feb-2021

No information available **Evaporation Rate** No information available Flammability Limit in Air No information available **Explosion Limits** Vapor pressure @20 °C (kPa) No information available Vapor density No information available 0.85 g/cm³ @15°C **Density** Solubility(ies) No information available **Partition coefficient** No information available **Autoignition Temperature** No information available

Kinematic viscosity @ 40C = 34.88 cSt; @ 100C = 7.33 cSt

Water solubility No information available

9.2. Other information

Decomposing Temperature

DMSO extract by IP346 Less than 3.0 wt% (mineral oil component only)

10. STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity The product is chemically stable.

10.2. Chemical stability

Chemical Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Possibility of Hazardous ReactionsNone under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

10.4. Conditions to avoid

Conditions to Avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible Materials Strong oxidizing agents

10.6. Hazardous decomposition products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and

vapors.

11. TOXICOLOGICAL INFORMATION

11.1 Information on likely routes of exposure

Inhalation May cause respiratory irritation.

Eye contact May cause slight irritation.

Skin Contact Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Ingestion May be harmful if swallowed.

11.2 Information on toxicological effects

Symptoms No information available

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Not classified.

Serious eye damage/eye

irritation

Not classified.

Sensitization May cause an allergic skin reaction. May cause sensitization of susceptible persons.

Mutagenic effects Not classified.

Reproductive Toxicity Not classified

STOT - single exposure Not classified.

STOT - repeated exposure Not classified

Aspiration hazard Not classified.

11.4 Carcinogenicity

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as

a known or anticipated carcinogen by NTP, IARC or ACGIH

Legend: NTP (National Toxicology Program), IARC (International Agency for Research on Cancer),

OSHA (Occupational Safety and Health Administration of the US Department of Labor),

Revision Date: 09-Feb-2021

ACGIH (American Conference of Governmental Industrial Hygienists)

11.5 Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Product Information (Estimated):

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-dust/mist) >5 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Long chain alkyl amine alkylene	-	> 2000 mg/kg (Rat)	-
amine			
64051-50-9			
Alkyl ester carboxylic acid	> 2,000 mg/kg (Rat)	> 3,160 mg/kg (Rabbit)	-
68015-93-0			

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Ecotoxicity effects Toxic to aquatic organisms. Harmful to aquatic life with long lasting effects. Plants and

animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil

layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

Revision Date: 09-Feb-2021

Chemical name	96h LC50 (fish - mg/L) (96HLCF)	48h EC50 (daphnia - mg/L) (48HLCD)	72h LC50 (algae - mg/L) (72HICA)
Long chain alkyl amine alkylene amine	101	73.4	101
Alkyl ester carboxylic acid		101	56

12.2 Persistence and degradability No information available.

12.3. Bioaccumulative potential No information available.

12.4 Mobility in Environmental Media No information available.

12.5 Other adverse effects: No information available.

PBT and vPvB assessment No information available

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Waste Disposal Method This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated packaging Dispose of in accordance with local regulations.

14.TRANSPORT INFORMATION

DOTNot regulatedIATANot regulatedIMDGNot regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	All ingredients are on the inventory or exempt from listing
DSL/NDSL	All ingredients are on the inventory or exempt from listing
ENCS	All ingredients are on the inventory or exempt from listing
IECSC	All ingredients are on the inventory or exempt from listing
KECL	All ingredients are on the inventory or exempt from listing
PICCS	All ingredients are on the inventory or exempt from listing
NZIoC	All ingredients are on the inventory or exempt from listing
REACH	All ingredients are on the inventory or exempt from listing

Revision Date: 09-Feb-2021

USA

Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazardous Categorization

Acute health hazardSkin SensitizerChronic Health HazardSkin Sensitizer

Fire hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical name	CAS-No	weight-%	RQ	TPQ
Methyl methacrylate	80-62-6	<0.1	RQ 1000lb final RQ	
			RQ 454kg final RQ	
Benzene	71-43-2	<0.001	RQ 10lb final RQ	
			RQ 4.54kg final RQ	

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical name	CAS-No	weight-%	HAPS data
Methyl methacrylate	80-62-6	<0.1	X
Benzene	71-43-2	< 0.001	X

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CAS-No	weight-%	U.S CWA (Clean Water Act)
Methyl methacrylate	80-62-6	<0.1	X
Benzene	71-43-2	<0.001	X

State Regulations

California Proposition 65

Label:

 \triangle

.WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Chemical name	CAS-No	weight-%	California Prop. 65	Maximum Allowable Dose	Safe Harbor Limits for
				for Reproductive	
				Toxicity	Chemicals
				(MADLS)	(NSRLs)

Revision Date: 09-Feb-2021

Instability: 0

Benzene	71-43-2	<0.001	Carcinogen	24µg/dayoral	6.4 µg/day oral
			Developmental	49µg/dayinhalation	13 µg/day inhalation
			Male Reproductive		

State Right-to-Know

Chemical name	CAS-No	weight-%	New Jersey
Alkenyl dicarboxylamide	EPA ACC. 147376	1-5	X
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	1-5	X
Amines, polyethylenepoly-, reaction products with succinic anhydride polybutenyl derivitives	68439-80-5	1-5	X
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	<1	X

Chemical name	CAS-No	weight-%	Massachusetts
Petroleum distillates, solvent dewaxed heavy	64742-65-0	1-5	X
paraffinic			

Chemical name	CAS-No	weight-%	Pennsylvania
Alkenyl dicarboxylamide	EPA ACC. 147376	1-5	X
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	1-5	X
Amines, polyethylenepoly-, reaction products with succinic anhydride polybutenyl derivitives	68439-80-5	1-5	Х

New Jersey Worker and Community Right-to-Know Act:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Automatic Transmission Fluid)

16. OTHER INFORMATION



Health hazards: 2

Prepared By: Latoya Walker

Revision Date: 09-Feb-2021

Revision Summary: Review

Section 1: Identification of the hazardous chemical and of the supplier

Flammability: 1

Section 15: REGULATORY INFORMATION

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet