

Safety Data Sheet

Hi-Tack Gasket Adhesive/Sealant

Section 1. Identification

Product Identifier Hi-Tack Gasket Adhesive/Sealant
Synonyms 39358
Manufacturer Stock Numbers 143328

Recommended use Refer to Technical Information
Uses advised against Refer to Technical Information

Manufacturer Contact Address
Dynatex a division of Soudal
350 Ring Road
Elizabethtown, KY, 42701
USA

Phone
(270) 769-3385

Emergency Phone
(800) 424-9300
CHEMTREC

Fax
(270) 765-2412

Section 2. Hazards Identification

Classification ACUTE TOXICITY - INHALATION - Category 5
ACUTE TOXICITY - ORAL - Category 4
ASPIRATION HAZARD - Category 2
EYE DAMAGE/IRRITATION - Category 2B
FLAMMABLE AEROSOLS - Category 1
SKIN CORROSION/IRRITATION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3

Signal Word Danger

Pictogram



Hazard Statements

Causes eye irritation
Causes skin irritation
Extremely flammable aerosol
Harmful if swallowed
May be harmful if inhaled
May be harmful if swallowed and enters airways
May cause drowsiness or dizziness.

Precautionary Statements

Response

Call a poison center/doctor if you feel unwell.
Do NOT induce vomiting.
If eye irritation persists: Get medical advice/attention.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF INHALED: Call a POISON CENTER or doctor if you feel unwell
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If on skin: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/attention.
If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center/doctor.
Read label before use.
Rinse mouth.
Take off contaminated clothing and wash it before reuse.

Prevention

Avoid breathing dust/fume/gas/mist/ vapors/spray.
Do not eat, drink or smoke when using this product.
Do not spray on an open flame or other ignition source.
Keep away from heat.
Pressurized container: Do not pierce or burn, even after use.
Use only outdoors or in a well-ventilated area.
Wash thoroughly after handling.
Wear protective gloves.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal

Dispose of contents/container in accordance with local, state and federal regulations.

Ingredients of unknown toxicity

0%

Hazards not Otherwise Classified

Additional Information

None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
110-54-3	Hexane	22% - 38%

67-64-1	2-Propanone	22% - 38%
68476-86-8	Liquified Petroleum Gas	20% - 30%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Eye Contact	Move to fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.
Skin Contact	Remove contaminated clothing and wash skin with soap and water. Get medical attention if irritation persists. Launder clothing before reuse.
Ingestion	Seek medical attention. DO NOT give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting.
Inhalation	Remove individual to fresh air. Give oxygen if breathing is labored. If breathing has stopped give artificial respiration. Keep person warm, quiet and seek medical attention.
Notes to Physician	Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Dry powder, foam, carbon dioxide.
Unsuitable Extinguishing Media	Water may be ineffective.
Flammability (per flame projection)	Extremely flammable
Unusual Fire or Explaion Hazards	Contents under pressure. Do not expose to temperatures exceeding 120° F as containers may vent, rupture or burst.
Special Fire Fighting Procedures	Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near area of use because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Water may be ineffective for extinguishment unless used under favorable conditions by experienced fire fighters. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Absorb spill with inert material then place in a chemical waste container. Dispose of spill material in accordance with regulations.

Section 7. Handling and Storage

Handling	DANGER! EXTREMELY FLAMMABLE. VAPOR HARMFUL. HARMFUL OR FATAL IF INHALED OR SWALLOWED. Contents under pressure. Keep away from heat, sparks, sources of ignition and open flames. Do not smoke while using or near area of use. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Use only in a well-ventilated area. Do not store at temperatures above 120°F. Intentional misuse by deliberately concentrating and inhaling the vapors (contents) may be harmful or fatal.
Storage	Keep out of reach of children. Do not store near heat, sparks, or open flames. Do not expose to temperatures above 120°F as container may vent, rupture or burst. Do not puncture or incinerate container. Do not store in direct sunlight. Store in a cool, dry, well-ventilated area away from incompatible materials. Store in accordance with NFPA 30B for Level 3 Aerosols.
Other Precautions	Read label precautions carefully. Follow label directions to avoid injury.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Hexane	50 ppm	500 ppm	1000 ppm
	2-Propanone	500 ppm TWA	1000 ppm TWA	750 ppm
	Liquified Petroleum Gas	1000 ppm	Not Est.	N/A
Personal Protective Equipment	N/A			
Ventilation	Local Exhaust: Maintain adequate ventilation. Mechanical (General):			
Respiratory Protection	Maintain exposure below exposure guidelines below levels that cause known, suspected or apparent adverse effects			
Eye Protection	Chemical goggles with side shields or face shield recommended.			
Protective Gloves	Chemical resistant gloves.			
Other Protective Clothing or Equipment	Wash hands after use and before eating, drinking, chewing gum or smoking.			
Other Precautions	Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.			

Section 9. Physical and Chemical Properties

Physical State	Aerosol spray can
Color	Opaque red liquid

Odor	Hydrocarbon
Odor Threshold	N/A
Solubility	Insoluble in water
Partition coefficient Water/n-octanol	N/A
VOC%	60.08%
Viscosity	Not established
Specific Gravity	0.76
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	<17C concentrate
FP Method	N/A
pH	N/A
Melting Point	N/A
Boiling Point	Not established
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	> 1.00 (BuAc=1)
Flammability	Flammable
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not established
Vapor Density	Not established

Note The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Chemical Stability	Stable
Hazardous polymerization	Will not occur
Conditions to Avoid	Open flames; Temperatures above 120F
Materials to Avoid	Concentrated nitric and sulfuric acid mixtures, oxidizing materials, chloroform, alkalis, chlorine compounds, acids, potassium t-butoxide
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide, hydrocarbons

Section 11. Toxicological Information

Carcinogenicity
Chronic Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.
Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Section 12. Ecological Information

Fate and Effects in Waste Water Treatment Plants Complete information is not yet available.
Environmental Effects Complete information is not yet available.
Environmental Fate and Distribution Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations, but contains SARA regulated substances. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number 1950
UN Proper Shipping Name Aerosols, flammable
DOT Classification 2.1
Packing Group Not applicable
IATA UN Number UN1950
UN proper shipping name Aerosols, flammable (ACETONE, HEPTANE)
Transport Hazard Class(es)
Class 2.1
Subsidiary risk ---
Label(s) 2.1
Packing group Not applicable
Environmental hazards No
Other information
Passenger and cargo aircraft Allowed
Cargo aircraft only Allowed
IMDG UN Number UN1950
UN proper shipping name Aerosols, flammable (ACETONE, HEPTANE)
Transport Hazard Class(es)

Class 2.1
Subsidiary risk ---
Label(s) 2.1
Packing group Not applicable
Environmental hazards
Marine Pollutant Yes

Section 15. Regulatory Information

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status

All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

California Proposition 65

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:
None known

Section 16. Other Information

Revision Date

9/10/2018

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.