

Revision Number: 004.0 Issue date: 08/21/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE 561 PIPE SEALANT STICK IDH number: 504467

known as PST(R) Thread Sealant

Stick

Product type:Anaerobic SealantItem number:37615Restriction of Use:None identifiedRegion:United States

Company address: Contact information:

Henkel Corporation Telephone: (860) 571-5100

One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing dust or fumes. Wash thoroughly after handling. Contaminated work clothing

should not be allowed out of the workplace. Wear eye and face protection. Wear protective

gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical

attention. Take off contaminated clothing.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 504467 Product name: LOCTITE 561 PIPE SEALANT STICK known as PST(R) Thread Sealant Stick Page 1 of 7

Hazardous Component(s)	CAS Number	Percentage*	
Polyglycoldioctanoate	Proprietary	30 - 60	
Polyglycol dimethacrylate	Proprietary	10 - 30	
Dimethacrylate ester	Proprietary	10 - 30	
Ethene, tetrafluoro-, homopolymer	9002-84-0	1 - 5	
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5	
Ethylene glycol	107-21-1	1 - 5	
Titanium dioxide	13463-67-7	1 - 5	
Saccharin	81-07-2	1 - 5	
Cumene hydroperoxide	80-15-9	0.1 - 1	
Cumene	98-82-8	0.1 - 1	

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. Get medical

attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

IDH number: 504467

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Irritating organic vapours. Oxides of carbon. Toxic fluorine compounds.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure

Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycoldioctanoate	None	None	None	None
Polyglycol dimethacrylate	None	None	None	None
Dimethacrylate ester	None	None	None	None
Ethene, tetrafluoro-, homopolymer	None	None	None	10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Ethylene glycol	100 mg/m3 Ceiling Aerosol.	None	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust.	None	None
Saccharin	None	None	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Cumene	50 ppm TWA	50 ppm (245 mg/m3) PEL (SKIN)	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:WaxColor:WhiteOdor:MildOdor threshold:Not available.pH:Not applicable

 Vapor pressure:
 < 10 mm hg (27 °C (80.6 °F))</td>

 Boiling point/range:
 > 149 °C (> 300.2 °F)

Melting point/ range: Not available.

IDH number: 504467 Product name: LOCTITE 561 PIPE SEALANT STICK known as PST(R) Thread Sealant Stick Page 3 of 7

Specific gravity: 1.1394 Vapor density: Not available. Flash point: Not applicable Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. **Evaporation rate:** Not available. Solubility in water: Slight

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not available.

1.06 %; 12.06 g/l
Not available.

Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

Hazardous decomposition

products:

IDH number: 504467

Oxides of carbon. Toxic fluorine compounds. Irritating organic vapours.

Incompatible materials: Strong oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system. Vapors

may cause headaches, nausea, dizziness and respiratory tract irritation.

Skin contact: Causes skin irritation. May cause allergic skin reaction.

Eye contact: Causes serious eye irritation.

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Polyglycoldioctanoate	None	Irritant	
Polyglycol dimethacrylate	None	Allergen, Irritant	
Dimethacrylate ester	None	Irritant, Allergen	
Ethene, tetrafluoro-, homopolymer	None	No Target Organs	
Silica, amorphous, fumed, crystal-free	None	Nuisance dust	
Ethylene glycol	Oral LD50 (RAT) = 5.89 g/kg Dermal LD50 (RABBIT) = 9,530 mg/kg	Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic	
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity	
Saccharin	None	No Target Organs	
Cumene hydroperoxide	None	Allergen, Central nervous system, Corrosive, Irritant, Mutagen	
Cumene	Oral LD50 (RAT) = 2.91 g/kg Oral LD50 (RAT) = 1,400 mg/kg Inhalation LC50 (RAT, 4 h) = 8000 ppm	Central nervous system, Irritant, Lung	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycoldioctanoate	No	No	No
Polyglycol dimethacrylate	No	No	No
Dimethacrylate ester	No	No	No
Ethene, tetrafluoro-, homopolymer	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Ethylene glycol	No	No	No
Titanium dioxide	No	Group 2B	No
Saccharin	No	No	No
Cumene hydroperoxide	No	No	No
Cumene	No	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 504467

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
None
Packing group:
Not regulated
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: Ethene, tetrafluoro-, homopolymer (CAS# 9002-84-0).

CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Ethylene glycol (CAS# 107-21-1). Saccharin (CAS# 81-07-2).

CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

Issue date: 08/21/2014

IDH number: 504467 Product name: LOCTITE 561 PIPE SEALANT STICK known as PST(R) Thread Sealant Stick Page 6 of 7

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.