Version 1.1	Revision Date: 2016-09-14		DS Number: 0010027905	Print Date: 2018-07-20 Date of last issue: 12.09.2016 Date of first issue: 14.09.2016		
SECTION 1	I. IDENTIFICATION					
Produc	ct name	:	: Shell Rotella T6 Multi Vehicle 5W-30			
Produc	ct code	:	001F8876			
Manufacturer or supplier's details						
Manuf	acturer/Supplier	:	Shell Canada Pro 400 - 4th Avenue Calgary AB T2P Canada	S.W		
Teleph Telefa:		:	(+1) 8006611600 (+1) 4033848345			
Emerg ber	ency telephone num-	:	UTEC (226-8832)	): (+1) 613-996-6666; Toll Free: 1-888-CAN- ) hr): 1 (703) 527-3887 or 1 (800) 424-9300		

## Recommended use of the chemical and restrictions on use

# **SECTION 2. HAZARDS IDENTIFICATION**

<b>GHS Classification</b> Chronic aquatic toxicity	: Category 3
GHS label elements	
Hazard pictograms	: No symbol
Signal word	: No signal word
Hazard statements	<ul> <li>PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: H412 Harmful to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	: <b>Prevention:</b> P273 Avoid release to the environment. <b>Response:</b> No precautionary phrases.
14	80001002790

Version	Revision Date:	SDS Number:	Print Date: 2018-07-20
1.1	2016-09-14	800010027905	Date of last issue: 12.09.2016
			Date of first issue: 14.09.2016

## Storage:

No precautionary phrases. **Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

## Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance name	: Shell Rotella T6 Multi Vehicle 5W-30
Chemical nature	<ul> <li>Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains &lt;3% (w/w) DMSO- extract, according to IP346. The highly refined mineral oil is only present as additive dilu- ent.</li> </ul>

### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Alkaryl amine	36878-20-3	1 - 3
Calcium sulphonate	70024-69-0	0.1 - 0.99
Alkyl borate	Not Assigned	0.1 - 0.99
Dialkyl alkaryl aminomethyl dicarboxylate	Not Assigned	0.1 - 0.99
Alkoxylated alcohol	68551-12-2	0.1 - 0.99
Distillates (Fischer - Tropsch), heavy, C18-50 -	848301-69-9	60 - 80
branched, cyclic and linear		

### **SECTION 4. FIRST-AID MEASURES**

General advice	: Not expected to be a health hazard when used under normal conditions.
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	: Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

Versic 1.1	on	Revision Date: 2016-09-14		DS Number: 00010027905	Print Date: 2018-07-20 Date of last issue: 12.09.2016 Date of first issue: 14.09.2016
а		nportant symptoms ects, both acute and d	:	of black pustules	s signs and symptoms may include formation and spots on the skin of exposed areas. sult in nausea, vomiting and/or diarrhoea.
Ρ	Protection of first-aiders		:		ing first aid, ensure that you are wearing the onal protective equipment according to the nd surroundings.
Ν	Notes t	o physician	:	Treat symptomati	ically.

# **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

# SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth
/ 14		800010027905

Version 1.1	Revision Date: 2016-09-14	SDS Number: 800010027905	Print Date: 2018-07-20 Date of last issue: 12.09.2016 Date of first issue: 14.09.2016		
		Soak up residue	ment material. lirectly or in an absorbent. e with an absorbent such as clay, sand or other al and dispose of properly.		
Additional advice		see Chapter 8 c For guidance or	<ul> <li>For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.</li> <li>For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.</li> </ul>		

# SECTION 7. HANDLING AND STORAGE

General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
Storage		
Other data	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

Version	Revision Date:	SDS Number:	Print Date: 2018-07-20
1.1	2016-09-14	800010027905	Date of last issue: 12.09.2016
			Date of first issue: 14.09.2016

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhal- able frac- tion))	5 mg/m3	US. ACGIH Threshold Limit Values
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

### **Biological occupational exposure limits**

No biological limit allocated.

## **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

 Engineering measures
 : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:<br/>Adequate ventilation to control airborne concentrations.

 Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

 General Information:<br/>Define procedures for safe handling and maintenance of controls.<br/>Educate and train workers in the hazards and control<br/>measures relevant to normal activities associated with this product.

Version 1.1	Revision Date: 2016-09-14	SDS Number: 800010027905	Print Date: 2018-07-20 Date of last issue: 12.09.2016 Date of first issue: 14.09.2016
		equipment used equipment, local Drain down syste nance. Retain drain dow subsequent recy Always observe washing hands a drinking, and/or s	good personal hygiene measures, such as after handling the material and before eating, smoking. Routinely wash work clothing and ment to remove contaminants. Discard con- ng and footwear that cannot be cleaned.
Perso	onal protective equip	nent	
Respi	ratory protection	conditions of use In accordance w tions should be t If engineering co tions to a level w select respiratory cific conditions o Check with respi Where air-filterin priate combination Select a filter sui	rotection is ordinarily required under normal e. ith good industrial hygiene practices, precau- aken to avoid breathing of material. ontrols do not maintain airborne concentra- thich is adequate to protect worker health, y protection equipment suitable for the spe- f use and meeting relevant legislation. ratory protective equipment suppliers. g respirators are suitable, select an appro- on of mask and filter. table for the combination of organic gases upe A/Type P boiling point >65°C (149°F)].
	protection marks	gloves approved US: F739) made suitable chemica gloves Suitability usage, e.g. frequ sistance of glove glove suppliers. Personal hygiene Gloves must only gloves, hands sh cation of a non-p For continuous of through time of r 480 minutes whe short-term/splash recognize that su may not be avail time maybe acce and replacement a good predictor	tact with the product may occur the use of to relevant standards (e.g. Europe: EN374, from the following materials may provide al protection. PVC, neoprene or nitrile rubber and durability of a glove is dependent on uency and duration of contact, chemical re- material, dexterity. Always seek advice from Contaminated gloves should be replaced. e is a key element of effective hand care. y be worn on clean hands. After using nould be washed and dried thoroughly. Appli- berfumed moisturizer is recommended. contact we recommend gloves with break- nore than 240 minutes with preference for > ere suitable gloves can be identified. For h protection we recommend the same, but uitable gloves offering this level of protection able and in this case a lower breakthrough eptable so long as appropriate maintenance t regimes are followed. Glove thickness is not of glove resistance to a chemical as it is e exact composition of the glove material.

Version 1.1	Revision Date: 2016-09-14	SDS Number: 800010027905	Print Date: 2018-07-20 Date of last issue: 12.09.2016 Date of first issue: 14.09.2016		
			s should be typically greater than 0.35 mm he glove make and model.		
Eye protection			: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.		
Skin and body protection		work clothes.	<ul> <li>Skin protection is not ordinarily required beyond standard work clothes.</li> <li>It is good practice to wear chemical resistant gloves.</li> </ul>		
Thern	nal hazards	: Not applicable	: Not applicable		
Prote	ctive measures		ctive equipment (PPE) should meet recom- al standards. Check with PPE suppliers.		
<b>_</b> .					

vant of the nece charg muni disch Loca	appropriate measures to fulfill the requirements of rele- environmental protection legislation. Avoid contamination e environment by following advice given in Chapter 6. If ssary, prevent undissolved material from being dis- ged to waste water. Waste water should be treated in a cipal or industrial waste water treatment plant before arge to surface water. I guidelines on emission limits for volatile substances be observed for the discharge of exhaust air containing ur.
--	--

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: Clear amber
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
рН	: Not applicable
pour point	: -54 °C / -65 °F Method: ASTM D97
Initial boiling point and boiling range	: > 280 °C / 536 °F estimated value(s)
Flash point	: 239 °C / 462 °F
	Method: ASTM D92 (COC)

Vers 1.1	sion	Revision Date: 2016-09-14	SDS Number: 800010027905		Print Date: 2018-07-20 Date of last issue: 12.09.2016 Date of first issue: 14.09.2016
	Evapor	ation rate	:	Data not availabl	e
	Flamma	ability (solid, gas)	:	Data not availabl	e
	Upper e	explosion limit	:	Typical 10 %(V)	
	Lower e	explosion limit	:	Typical 1 %(V)	
	Vapour	pressure	:	< 0.5 Pa (20 °C / estimated value(	
	Relative	e vapour density	:	> 1 estimated value(	s)
	Relative	e density	:	0.845 (15 °C / 59	)°F)
	Density	,	:	845 kg/m3 (15.0	°C / 59.0 °F)Method: ASTM D4052
	Solubili Wate	ty(ies) er solubility	:	negligible	
	Solu	bility in other solvents	:	Data not availabl	e
	Partitio octanol	n coefficient: n- /water	:	Pow: > 6 (based on inform	ation on similar products)
	Auto-ig	nition temperature	:	> 320 °C / 608 °F	=
	Viscosi Visco	ty osity, dynamic	:	Data not availabl	e
	Visco	osity, kinematic	:	75 mm2/s (40.0 ° Method: ASTM D	
				12.1 mm2/s (100 Method: ASTM D	
	Explosi	ve properties	:	Not classified	
	Oxidiziı	ng properties	:	Data not availabl	e
	Conduc	ctivity	:	This material is n	not expected to be a static accumulator.
	Decom	position temperature	:	Data not availabl	e

# SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
/ 14	800010027905

Version 1.1	Revision Date: 2016-09-14	SDS Num 80001002	
Pos tion	sibility of hazardous reac s	- : Read	cts with strong oxidising agents.
Cor	ditions to avoid	: Extre	emes of temperature and direct sunlight.
Inco	mpatible materials	: Stror	ng oxidising agents.
	ardous decomposition lucts		ardous decomposition products are not expected to form ng normal storage.

# SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
	whole, rather than for individual component(s).

### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

## Acute toxicity

### Product:

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	:	Remarks: Not considered to be an inhalation hazard under normal conditions of use.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Expected to be of low toxicity:

### Skin corrosion/irritation

## Product:

Remarks: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

### Serious eye damage/eye irritation

### Product:

Remarks: Expected to be slightly irritating.

## Respiratory or skin sensitisation

# Product:

Remarks: Not expected to be a skin sensitiser.

Version	Revision Date:	SDS Number:
1.1	2016-09-14	800010027905

Print Date: 2018-07-20 Date of last issue: 12.09.2016 Date of first issue: 14.09.2016

# Components:

#### Calcium sulphonate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

### Alkyl borate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

### Dialkyl alkaryl aminomethyl dicarboxylate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vivo

: Remarks: Not considered a mutagenic hazard.

### Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

### **Reproductive toxicity**

### Product:

Effects on fertility

Remarks: Not expected to impair fertility. Not expected to be a developmental toxicant.

## STOT - single exposure

## Product: Remarks: Not expected to be a hazard.

## STOT - repeated exposure

### Product:

Remarks: Not expected to be a hazard.

## Aspiration toxicity

## Product:

Not considered an aspiration hazard.

Version 1.1	Revision Date: 2016-09-14	SDS Number: 800010027905	Print Date: 2018-07-20 Date of last issue: 12.09.2016 Date of first issue: 14.09.2016
			Date of first issue: 14.09.2016

### Further information

### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

## **SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity		
Product: Toxicity to fish (Acute toxici- ty)	:	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l
Toxicity to crustacean (Acute toxicity)	:	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l
Toxicity to algae/aquatic plants (Acute toxicity)	:	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l
Toxicity to fish (Chronic tox- icity)	:	Remarks: Data not available
Toxicity to crustacean	:	Remarks: Data not available
(Chronic toxicity) Toxicity to microorganisms (Acute toxicity)	:	Remarks: Data not available
Persistence and degradability	у	
Product:		
Biodegradability	:	Remarks: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegrada- ble, but contains components that may persist in the environ-
/ 14		800010027905

ersion 1	Revision Date: 2016-09-14	SDS Number: 800010027905	Print Date: 2018-07-20 Date of last issue: 12.09.2016 Date of first issue: 14.09.2016	
		ment.		
Bioa	ccumulative potentia	I		
Prod	uct:			
Bioac	ccumulation	: Remarks: Con cumulate.	: Remarks: Contains components with the potential to bioac- cumulate.	
	ion coefficient: n- ol/water	: Pow: > 6 Remarks: (bas	: Pow: > 6 Remarks: (based on information on similar products)	
Mobi	lity in soil			
Prod	uct:			
Mobility			id under most environmental conditions. , it will adsorb to soil particles and will not be	
		Remarks: Floa	ats on water.	
Othe	r adverse effects			
Prod	uct:			
Additional ecological infor- mation		expected to be Not expected	ixture of non-volatile components, which are not ereleased to air in any significant quantities. to have ozone depletion potential, photochemi- ation potential or global warming potential.	
		Poorly soluble May cause ph	mixture. ysical fouling of aquatic organisms.	

<b>Disposal methods</b> Waste from residues	: Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
	Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or na- tional requirements and must be complied with.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Version	Revision Date:	SDS Number:	Print I
1.1	2016-09-14	800010027905	Date
			Date

Print Date: 2018-07-20 Date of last issue: 12.09.2016 Date of first issue: 14.09.2016

### **SECTION 14. TRANSPORT INFORMATION**

### **National Regulations**

TDG

Not regulated as a dangerous good

### **International Regulations**

### IATA-DGR

Not regulated as a dangerous good

## IMDG-Code

Not regulated as a dangerous good

# Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category Ship type Product name Special precautions	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
Special precautions for user	
Remarks	: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
Additional Information	: MARPOL Annex 1 rules apply for bulk shipments by sea.

# **SECTION 15. REGULATORY INFORMATION**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

## The components of this product are reported in the following inventories:

EINECS	: Not established.
TSCA	: All components listed.
DSL	: Not established.

## **SECTION 16. OTHER INFORMATION**

## Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -

Version	Revision Date:	SDS Number:	Print Date: 2018-07-20
1.1	2016-09-14	800010027905	Date of last issue: 12.09.2016 Date of first issue: 14.09.2016

Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada): ECx - Concentration associated with x% response: ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version. Revision Date : 2016-09-14

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN